

AD-A126 320

PHASE 2B PROTOTYPE REDESIGN TACTICAL RUBIDIUM FREQUENCY
STANDARD(U) EG AND G INC SALEM MA ELECTRONIC COMPONENTS
DIV W J RILEY JAN 83 RADC-TR-83-8 F19628-82-C-0055

1/1


UNCLASSIFIED

F/G 14/2

NL



END
FILMED
FBI
BTIC



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

WA 126320

RADC-TR-83-8
Final Technical Report
January 1983



12

PHASE 2B PROTOTYPE REDESIGN, TACTICAL RUBIDIUM FREQUENCY STANDARD

EG&G Electronic Components

William J. Riley

DTIC
ELECTE
APR 4 1983
S B

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED

ROME AIR DEVELOPMENT CENTER
Air Force Systems Command
Griffiss Air Force Base, NY 13441

DTIC FILE COPY

83 04 04 04 1

This report has been reviewed by the RADC Public Affairs Office (PA) and is releasable to the National Technical Information Service (NTIS). At NTIS it will be releasable to the general public, including foreign nations.

RADC-TR-83-8 has been reviewed and is approved for publication.

APPROVED: *Ferdinand Euler*

FERDINAND K. EULER
Project Engineer

APPROVED:

Harold Roth

HAROLD ROTH
Director, Solid State Sciences Division

FOR THE COMMANDER:

John P. Huss

JOHN P. HUSS
Acting Chief, Plans Office

If your address has changed or if you wish to be removed from the RADC mailing list, or if the addressee is no longer employed by your organization, please notify RADC (ESES) Hanscom AFB MA 01731. This will assist us in maintaining a current mailing list.

Do not return copies of this report unless contractual obligations or notices on a specific document requires that it be returned.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER RADC-TR-83-8	2. GOVT ACCESSION NO. AD-A126320	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) PHASE 2B PROTOTYPE REDESIGN, TACTICAL RUBIDIUM FREQUENCY STANDARD		5. TYPE OF REPORT & PERIOD COVERED Final Technical Report 16 Jun - 16 Oct 82
		6. PERFORMING ORG. REPORT NUMBER N/A
7. AUTHOR(s) William J. Riley		8. CONTRACT OR GRANT NUMBER(s) F19628-82-C-0055
9. PERFORMING ORGANIZATION NAME AND ADDRESS EG&G Electronic Components Division 35 Congress Street Salem MA 01970		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 63727F 22770011
11. CONTROLLING OFFICE NAME AND ADDRESS Rome Air Development Center (ESES) Hanscom AFB MA 01731		12. REPORT DATE January 1983
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) Same		13. NUMBER OF PAGES 14
		18. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE N/A
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report) Same		
18. SUPPLEMENTARY NOTES RADC Project Engineer: Ferdinand K. Euler (ESES)		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Rubidium Frequency Standard Miniaturization High Precision Militarization Fast Warm-Up		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) This report summarizes the progress made during Phase 2B of an effort to develop a tactical rubidium frequency standard (TRFS) for the U.S. Air Force SEEK TALK program. The overall objective is to achieve a production capability for an extremely small, rugged and fast warmup atomic clock for avionics applications. This phase of the program accomplished the redesign of the previous bench version into a prototype configuration. Projected prototype size is 2.5 x 2.5 x 4.0 inches.		


DD FORM 1 JAN 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)



UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

1.0 INTRODUCTION

This report summarizes the progress made during Phase 2B of an effort to develop a tactical rubidium frequency standard (TRFS) for the U.S. Air Force SEEK TALK program. The overall objective is to achieve a production capability for an extremely small, rugged and fast warmup atomic clock for avionics applications. This phase of the program accomplished the redesign of the previous bench version into a prototype configuration.

Accession For	
NTIS GRA&I	<input checked="checked" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A	



2.0 OVERALL DESIGN PROGRESS

The TRFS design approach was first described in an EG&G technical proposal in June, 1981⁽¹⁾. Phase 2A of the program then accomplished the design, fabrication and test of a working bench version. The results of that work were described in a final report in July, 1982⁽²⁾. The current effort involved redesign of the bench version into a prototype configuration. It is expected that future work under Phase 2C will involve the building and test of two prototype units.

(1) EG&G, Volume I Technical Proposal, Tactical Rubidium Frequency Standard (TRFS) for the SEEK TALK Program, June 19, 1981.

(2) Final Report, Phase 2A Bench Model Development, Tactical Rubidium Frequency Standard, 16 July 1982.

3.0 PROTOTYPE REDESIGN

The prototype redesign activities involved improvements as a result of bench unit testing and repackaging to allow the complete unit to be built inside a 2½ inch by 4 inch enclosure.

The only conceptual change from the bench version is the replacement of the 180 MHz VCO with a 90 MHz crystal oscillator and doubler. This change is shown in the VHF section of the revised block diagram of Figure 1. The advantages of this approach were described in Section 8.0 of the Phase 2A final report.

Otherwise, the prototype redesign effort has primarily involved repackaging as shown in Figure 2. The major repackaging task was to move the 20 MHz crystal oscillator inside the physics package. This allows the quartz crystal to share the temperature controlled environment of the microwave cavity and makes feasible the overall prototype packaging concept. A new layout was also done for the servo amplifier board using SIP resistor networks to save space. This is the densest board and thus establishes that the electronic circuits will all fit into the allocated space.

Improvements were also made inside the physics package. New absorption cells were made with a revised buffer gas mix ratio for better temperature coefficient. Improvements were made in the microwave multiplier for smoother behavior and increased output. Lamp exciter experiments were conducted to verify and improve the pumping light source during starting and running. A cross-sectional view of the physics package is shown in Figure 3, and Figure 4 is a photograph of its major components.

4.0 REDESIGN RESULTS

The redesign effort has resulted in verification of the original packaging concept that has size and weight advantages over existing designs while complying with all performance requirements.

The completely packaged unit will include covers and circuit board coatings that will insure compliance with the humidity, salt fog, sand, dust, fungus, explosive atmosphere, acoustical noise, and vibration requirements.

The complete unit will contain magnetic and metallic shields, electrical filters, and electronic suppressor devices to insure compliance with the electromagnetic interference and transient voltage requirements.

The TRFS will use electronic regulation of the internal voltages and lamp exciter current to insure compliance with the supply voltage ripple requirements. The most critical aspect is the susceptibility of the lamp exciter circuit.

The design includes monitors for the light, signal, and control voltage signals, as well as a lock status indicator. These are built-in test and maintenance provisions. The electronic circuits yield a MTBF prediction of about 30,000 hours in an airborne uninhabited environment with JANTX and 883B quality level active components.

The mechanical design includes consideration of the demands placed on materials and processes to withstand shock, vibration, bench handling, and on-off cycling. The most critical vibration problem is associated with the acceleration sensitivity of the quartz crystal and the resulting

degradation of spectral purity.

The baseline TRFS design is directed toward an upper baseplate temperature of $+71^{\circ}\text{C}$. If it is necessary to operate at a higher temperature (such as the $+80^{\circ}\text{C}$ called for by Hazeltine in their SEEK-TALK FSU specifications) additional redesign will be required. This may take the form of thermoelectric cooling and a larger overall package size.

An effective means of frequency synchronization was described in the original proposal as a design option. Since there is no operational need for this feature, it is not part of the baseline design.




Figure 1. TRFS Block Diagram.




Figure 2. TRFS Packaging Layout.




Figure 3. Layout of Miniaturized Physics Package.




Figure 4. Physics Package Parts.

Rome Air Development Center

RADC plans and executes research, development, test and selected acquisition programs in support of Command, Control, Communications and Intelligence (C³I) systems. Technical and engineering support within areas of technical competence is provided to ESD Program Offices (POs) and other ESD elements. The principal technical mission areas are: communications, electromagnetic guidance and control, surveillance of ground and aerospace objects, intelligence data collection and handling, information system technology, ionospheric propagation, solid state sciences, microwave physics and electronic reliability, maintainability and compatibility.